

750/850W

M12II Bronze


EVO EDITION



The Ultimate Modular Power Supply

Special Features


- DC to DC Converter Design
- Highly Reliable 105°C Aluminum Electrolytic Capacitors
- Smart and Silent Fan Control [S²FC]
- Active Power Factor Correction [up to 99%]
- Ample +12V Output
- 120mm Fluid Dynamic Bearing (FDB) Fans
- Multi-GPU Technology Support
- Fully Modular Cables
- Ultra Ventilation [Honeycomb Structure]
- Gold Plated High Current Terminals
- Multi-GPU Technology Support
- Soft-Rubber Mounting Cushions
- Universal AC Input [Full Range]
- 5 Years Warranty



Honeycomb Structure




High Quality 105°C E-CAP



120mm Fluid Dynamic Bearing (FDB) Fans



DC to DC Converter Design



Flexible Modular Cables



Power Distribution

Model	+3.3V	+5V	+12V	-12V	+5Vsb	Total Power
M12II-750 Bronze	25A	25A	62A	0.5A	3A	750W
	150W		744W	6W	15W	
M12II-850 Bronze	25A	25A	70A	0.5A	3A	850W
	150W		840W	6W	15W	

Wire Configuration

Cable							
Model	Main Power (20 / 24P) 600mm	EPS12V / ATX12V (8P / 4P) 650mm	EPS12V (8P) 650mm	PCI-E (6P / 8P) 600mm	SATA	Peripheral (4P)	FDD(4P) (Y-adaptor)
M12II-750 Bronze	1	1	1	6	10	5	1
M12II-850 Bronze	1	1	1	6	10	5	1



Safety & EMI / EMC

Protection Features: OCP / OPP / OTP / OVP / SCP / UVP

Specifications may change without prior notice



Headquarters tel: +886-2-2659-0338 fax: +886-2-2659-0530 sales@seasonic.com.tw www.seasonic.com
 USA Subsidiary tel: +1 626-969-9966 fax: +1 626-969-9986 usa@seasonic.com www.seasonicusa.com
 Europe Subsidiary info@seasoniceu.com

520 / 620W


M12II **Bronze** EVO EDITION

The Ultimate Modular Power Supply



Special Features


- Highly Reliable 105°C Aluminum Electrolytic Capacitors
- Smart and Silent Fan Control [S²FC]
- Active Power Factor Correction [up to 99%]
- Ample +12V Output
- 120mm Fluid Dynamic Bearing (FDB) Fans
- Multi-GPU Technology Support
- Fully Modular Cables
- Ultra Ventilation [Honeycomb Structure]
- Gold Plated High Current Terminals
- Multi-GPU Technology Support
- Soft-Rubber Mounting Cushions
- Universal AC Input [Full Range]
- 5 Years Warranty




Honeycomb Structure



High Quality 105°C E-CAP



120mm Fluid Dynamic Bearing (FDB) Fans



Flexible Modular Cables

Power Distribution

Model	+3.3V	+5V	+12V	-12V	+5Vsb	Total Power
M12II-520 Bronze	24A	24A	40A	0.8A	2.5A	520W
	130W		480W	9.6W	12.5W	
M12II-620 Bronze	24A	24A	48A	0.8A	2.5A	620W
	130W		576W	9.6W	12.5W	

Wire Configuration

Cable						
Model	Main Power (20 / 24P) 600mm	EPS12V / ATX12V (8P / 4P) 650mm	PCI-E (6P / 8P) 600mm	SATA	Peripheral (4P)	FDD(4P) (Y-adapter)
M12II-520 Bronze	1	1	2	6	5	1
M12II-620 Bronze	1	1	4	8	5	1



Safety & EMI / EMC

Protection Features: OPP / OVP / SCP / UVP

Specifications may change without prior notice



Headquarters tel: +886-2-2659-0338 fax: +886-2-2659-0530 sales@seasonic.com.tw www.seasonic.com
 USA Subsidiary tel: +1 626-969-9966 fax: +1 626-969-9986 usa@seasonic.com www.seasonicusa.com
 Europe Subsidiary info@seasoniceu.com